

Warehouse GateWay



Technical specifications

Applications

- Cold chain monitoring (EN 12830, EN 13485)
- Remote monitoring
- Routes wireless data from Seemoto sensors to the service

Installation places

- Buildings, warehouses, retail shops, vehicles...
- Universal device for all types of properties and buildings

Benefits

- Enables wireless communication around building environment
- Connects sensors and controls wirelessly
- Reliable, secure and maintenance-free
- Easy to install - possibility to upgrade later with new sensors

Size and weight

- Size: 105 x 65 x 17 mm
- Weight: 73 g

Features

- GSM/GPRS/EDGE 850/900/1800/1900, MSC10 (Telit GE865-QUAD module)
- GPS location information
- Lightweight and durable enclosure

Usage

- Various installation options
- Operating temperature -40 °C ... +85 °C
- Power input 100–240 V AC, 50/60 Hz (via AC adapter)
- Remote control, configuration and diagnostics
- Remote software update

Standards

- EN 301 489-1 / -7 / -17 and directive 2006/28/EC
- EN 300 328
- EN 61010-1
- Complies with 2014/53/EU (RED) and 2011/65/EU (RoHS)
- Fulfills together with TS sensor
- EN 12830:1999; S; T; C; D; 1
- EN 13485:2001